

tesa[®] 7106 **Optical Clear Adhesive**



Product Information

150µm pressure sensitive optically clear tape with mura resistant feature

Product Description

tesa® 7106 is a highly transparent transfer tape produced for optically clear lamination on rigid or flexible substrates. It is developed for medium to big size display with glass cover lamination to LCD panel. It is an optically clear adhesive tape with pressure sensitive design.

Product Features

- · Pressure sensitive design
- Good gap filling property
- · Laminate glass with rigid display like LCD without Mura/optical distortion
- Superior temperature, humidity and UV resistance

Application Fields

optically clear lamination on rigid or flexible substrates

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	none		Color	transparent		
•	Type of adhesive	acrylic	٠	Color of liner	transparent		
•	Type of liner	PET film	•	Thickness of easy release liner	75 µm		
•	Total thickness	150 μm	•	Thickness of tight release liner	75 µm		
Product Assortment							

Product Assortment

Available colors	transparent							
Properties/Performance Values								
Ageing resistance (UV)HazeHumidity resistance	0.1 % • very good	 Refractive index Temperature resistance long term Transmittance (380 - 780nm) > 	1.48 105 °C 99 %					
Adhesion to Values								
Glass (initial)PC (initial)	04.N//	PET (initial)Polarizer (initial)	7.1 N/cm 7.1 N/cm					

For latest information on this product please visit http://l.tesa.com/?ip=07106



tesa® 7106 Optical Clear Adhesive

Product Information

Additional Information

Easy liner outside in logroll

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 07/06/24 – en-US